



Anchor Kit for use with ASP Tripod and Systems

Three 18" Penetrators



Three Tie-Off Cables with loop ends



Single Ratchet T-Handle



Items Not to Scale

Anchor Kit

Keep your solar power supply secure and steady with this additional kit. Install with your solar set up and weather rain, wind, snow, and storm.

Includes three 18" Penetration Aluminium Screw Anchors, three Galvanized Aircraft Tie-Off Cables with loop ends, and one ratcheting T-Handle Driver with 1" socket for installation.

| Specifications | ASP Anchor Kit |
|-----------------------------------|---|
| Penetrator Material | Aircraft-quality cast aluminum 356 alloy |
| Penetration Depth | 18" |
| Penetrator Diameter | 1" Neck, 1.75" Flight, 2" Flange |
| Penetrator Socket Size | 1" |
| Penetrator Weight | 1.5 lb each |
| Head Shape | 6-point or hex head |
| Pullout Strength (fully embedded) | 2,500 lb hardpan or asphalt; 1,700 Soil Class 1 (dense sand or gravel); 600 lb Soil Class 2 (medium sandy gravel); 350 lb Soil Class 3 (loose medium-to-fine sand); 200 lb Soil Class 4 (loose fine uncompacted sand) |
| Cable Dimensions | 1/4" x 15" Galvanized Aircraft Cable |
| Included Installation Tool | Racheting T-Handle Driver, 1" socket |